


Dvouřadé válečkové řetězy - dle DIN 8188 (Americké), ISO - R 606, ČSN 02 3311

Zweifach Rollenketten - nach DIN 8188 (Amerikanische Bauart), ISO - R 606

Duplex roller chains - to DIN 8188 (American series), ISO - R 606

Двухрядные роликовые цепи – согласно DIN 8188 (американские), ISO – R 606, ГОСТ 10947-64



ISO Nr. ISO Nr. St. ISO	ANSI	Obj. čís. Art. Nr. Part no. Код для заказа	p mm	b ₁ mm min.	b ₂ mm max.	d ₁ mm h9	d ₃ mm h10	l ₁ mm	l ₂ mm	g mm	s ₁ mm	s ₂ mm	e mm	f mm ²	F _B kN min.	Q kg/m
08A-2	40-2	318 112 069 000	12,700	7,85	11,15	3,96	7,95	32,3	36,2	12,0	1,6	1,6	14,38	88	28,2	1,2
10A-2	50-2	318 112 089 000	15,875	9,40	13,80	5,08	10,16	39,9	44,0	15,0	2,0	2,0	18,11	140	44,4	1,9
12A-2	60-2	318 112 109 000	19,050	12,57	17,70	5,94	11,91	49,8	44,4	18,0	2,4	2,4	22,78	210	63,6	2,9
16A-2	80-2	318 112 129 000	25,400	15,75	22,50	7,92	15,88	62,7	68,1	24,1	3,0	3,0	29,29	356	113	5,0
20A-2	100-2	318 112 149 000	31,750	18,90	27,40	9,53	19,05	76,4	81,2	29,4	4,0	4,0	35,76	522	177,0	7,9
24A-2	120-2	318 112 169 000	38,100	25,22	35,30	11,10	22,23	96,3	100,9	35,0	5,0	5,0	45,44	784	254,0	11,8
28A-2 ¹⁾	140-2	318 112 189 000	44,450	25,22	37,00	12,70	25,40	102,8	108,2	41,0	5,5	5,5	48,87	940	344,8	13,8
32A-2 ¹⁾	160-2	318 112 209 000	50,800	31,55	45,00	14,27	28,58	124,0	128,2	47,0	6,5	6,5	58,55	1284	453,6	19,9
40A-2 ¹⁾	200-2	318 112 229 000	63,500	37,85	54,70	19,84	39,68	151,0	157,0	59,0	8,0	8,0	71,55	2170	707,6	33,0
48A-2 ¹⁾	240-2	318 112 249 000	76,200	47,35	67,50	23,80	47,63	183,0	191,0	70,0	9,5	9,5	87,83	3213	1020,6	44,0

1) Plná pouzdra

Na požádání:
zinkované provedení
niklované provedení

1) Buchsen von nahtlosen Röhren

Auf Wunsch:
verzinkte Ausführung
vernikkelte Ausführung

1) Solid bushes

Upon request:
zinc plating execution
nickel plating execution

1) Сплошные втулки

По требованию:
оцинкованное исполнение
никелированное исполнение

